

特色：

- ▲合成膜製程生物相容性佳
- ▲Potting特殊鏡面處理，血液不易凝結
- ▲有效移除低分子量蛋白，Albumin loss低
- ▲β 2-MG清除效率高達70%以上
- ▲磷清除率高能有效減少搔癢症狀
- ▲r-ray消毒，安全性佳

Performance

*1 Clearance (mL/min)	*SF-50UH	SF-70UH	SF-90UH	SF-110UH	SF-130UH	SF-150UH	SF-170UH	SF-190UH	SF-210UH	SF-250UH
Urea	166	181	189	194	197	198	199	199	200	200
Creatinine	145	165	177	185	190	193	195	197	198	199
Phosphate	143	162	175	183	188	192	194	196	197	199
Vitamin B ₁₂	85	106	122	135	145	154	161	167	172	180
Myoglobin	35	43	51	57	63	69	75	81	87	96
*2 UFR (mL/hr/100mmHg)	1,670	2,340	3,000	3,670	4,340	5,010	5,680	6,350	7,010	8,350

*1 In Vitro Test Condition : Dialyzer Performance Evaluation Standards of the Japanese Society for Artificial Organs,
Qb 200mL/min, Qd 500mL/min, Qf 10mL/min, 37°C

*2 UFR : Typical Clinical Data

*3 "SF" is the abbreviated name for "SUREFLUX™"

Specification

	SF-50UH	SF-70UH	SF-90UH	SF-110UH	SF-130UH	SF-150UH	SF-170UH	SF-190UH	SF-210UH	SF-250UH
Effective Surface Area (m ²)	0.5	0.7	0.9	1.1	1.3	1.5	1.7	1.9	2.1	2.5
Priming Volume (mL)	35	45	55	65	75	90	105	115	125	145
Effective Length (mm)	165	176	191	205	216	227	236	245	254	280
Inner Diameter (μm)	200									
Membrane Thickness (μm)	15									
Maximum TMP (mmHg)	500									
Materials	Membrane	Triacetate								
	Housing	Polycarbonate								
	Header	Polycarbonate								
	Potting Compound	Polyurethane								
Sterilization	Gamma Ray									
Package	24 Pcs/Carton									